

Zoom95 Series

Robotic Total Station



Modern data handling

- Large 5" VGA touch screen
- Powerful processor - easy & fast handling of big files
- Automatic data backup
- Scout: Quick search for passive prisms within a large area

Maximum flexibility

- Field software: X-PAD Ultimate Survey or Build on Android, X-PAD Survey or Construction on Windows Mobile
- Field controllers: GeoMax' or your own device

Smart Investment

- No maintenance cost for field software
- Latest Hexagon technology
- Stress-free equipment: PIN/PUK - anti-theft feature



Scan to find out more on the
Zoom95 Product Page



geomax-positioning.com

©2021 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved.

Zoom95 Series

Zoom95 is the perfect one-person total station.

If you are in charge of surveying for construction projects or purchasing devices for your company, this one-person total station is made for you. The prism can be quickly located, tracked and stays locked with the built-in STReAM360 technology.

Combined with our X-PAD field software, which is open to 3rdparty field controllers and available in Windows and Android, Zoom95 provides a full range of efficient choices. X-PAD software suite has been developed based on our customer feedback. It perfectly matches Zoom95 workflows. It is so easy to use that no extra training is needed.

This solution is not only economical, with no maintenance cost, but your data is digitalised, secure and easy to access.

ANGLE MEASUREMENTS

Accuracy	1" (0.3 mgon), 2" (0.6 mgon), 3" (1.0 mgon), 5" (1.5mgon)
Display resolution	0.1" (0.1 mgon)
Method	Absolute, continuous, diametrical
Compensation	Quadruple axis

TELESCOPE

Magnification	30x
---------------	-----

DISTANCE MEASUREMENTS TO STD. PRISM ACCURACY/TIME (TYPICAL)

Single (fast)	2 mm + 1.5 ppm / 0.8s
Standard	1 mm + 1.5 ppm / 2.4s
Continuous	3 mm + 1.5 ppm / < 0.15s
Range	up to 3500m

DISTANCE MEASUREMENTS - REFLECTORLESS

Range	accXess5 / accXXess10 500 m / 1000 m
Accuracy	2 mm + 2 ppm*
Time	Typ. 2-6 sec
Precise capture	8x20 mm at 50 m

INTERFACE

Keyboard	Full alphanumeric; 25 keys; illuminated (2nd optional)
Display	5" WVGA 800x480 colour and touch with LED backlight
Data recording	2 GB internal memory; removable SD card and USB stick
Ports	Serial; USB; internal Bluetooth®; long-range Bluetooth handle External power and WLAN
Operating system	Microsoft® Windows® EC 7.0

MOTORISATION

Technology	Hybrid Drives
------------	---------------

GeoTRail - GNSS based prism search

Speed	100 g/sec
-------	-----------

Scout - Opto-electronic prism search

Range	300 m at round prism
-------	----------------------

TRack - Automatic prism logging

Range	800 m at round prism
-------	----------------------

Max speed	90 km/h at 100m
-----------	-----------------

AiM - Automatic prism fine aiming

Range	1,000 m at round prism
-------	------------------------

Hz/V accuracy	1"
---------------	----

Technique	Image processing
-----------	------------------

NAVLIGHT™ - ALIGNMENT AID

Range	5 m to 150 m
-------	--------------

Accuracy	5 cm at 100 m
----------	---------------

PHYSICAL SPECIFICATIONS

Weight	5.0 - 5.3 kg (w/o battery and tribrach)
--------	--

Operating- / storage temperature	-20° C to 50° C / -40° C to 70° C
-------------------------------------	--------------------------------------

Protection class	IP55 dust and waterproof rating
------------------	---------------------------------

Humidity	95%, non-condensing
----------	---------------------

POWER SUPPLY

Internal battery	Removable Li-Ion 4.4 Ah / 7.4 V
------------------	---------------------------------

Operating time	Up to 8 h**
----------------	-------------

PLUMMET

Type	Laser point, adjustable brightness
------	------------------------------------

Accuracy	1.5 mm at 1.5 m instrument height
----------	-----------------------------------

* > 500 m: 4 mm + 2 ppm;

** Battery time may be shorter depending on conditions.



Main Office:
4317 Park Drive Ste 104
Norcross, GA 30093
www.egps.net

o: 770.695.3361
f: 770.695.0803
info@egps.net

GOLD STATUS GEOMAX-AUTHORIZED
TOTAL STATION, ROBOTICS & GPS SERVICE CENTER

GEOMAX Authorised Distribution Partner



Vertical laser fan emitted from rotating instrument Scouts prism.
Target continuously TRacked. Accurate AiMing at any prism, without
looking through telescope.



Distance meter (Prism Mode): Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1; **Laser plummet:** Laser class 2 in accordance with IEC 60825-1 resp. EN 60825-1.



Distance meter (Non-Prism Mode accXess): Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1



Copyright GeoMax AG.

Illustrations, descriptions and technical specifications are not binding and may change.

All trademarks and trade names are those of their respective owners.

06/21 952860 en