

Zoom75 Series

Robotic Total Station



Modern data handling

- Large 5" VGA touch screen
- Powerful processor - easy & fast handling of big files
- Automatic data backup
- GeoTRail prism search

Maximum flexibility

- Field software: running on Android devices
- Field controllers: GeoMax' or your own device

Smart Investment

- No maintenance cost for field software
- Latest Hexagon technology
- Stress-free equipment: PIN/PUK - anti-theft feature



Scan to find out more on the
Zoom75 Product Page



[geomax-positioning.com](https://www.geomax-positioning.com)

©2021 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved.

Zoom75 Series

The solution to digitalise your site

Zoom75 with X-PAD is the right solution to digitalize your site

The Zoom75 and X-PAD solution was developed to meet the demands of both novice and experienced surveyors. You can use two people and the onboard software or a single surveyor with a field controller or a phone. Both guarantee fast and convenient work with CAD data. The instrument's big screen, optional long-range Bluetooth handle, and high-performing processor add to the easy, intuitive workflow of X-PAD software. Available for Android devices, X-PAD provides a familiar user experience, reducing the need for training.

In addition, software maintenance for X-PAD Ultimate comes at no extra cost.

ANGLE MEASUREMENTS

Accuracy	1" (0.3 mgon), 2" (0.6 mgon), 3" (1.0 mgon), 5" (1.5mgon)
Display resolution	0.1" (0.1 mgon)
Method	Absolute, continuous, diametrical
Compensation	Quadruple axis

TELESCOPE

Magnification	30x
---------------	-----

DISTANCE MEASUREMENTS TO STD. PRISM ACCURACY/TIME (TYPICAL)

Single (fast)	2 mm + 1.5 ppm / 0.8s
Standard	1 mm + 1.5 ppm / 2.4s
Continuous	3 mm + 1.5 ppm / < 0.15s
Range	up to 3500m

DISTANCE MEASUREMENTS - REFLECTORLESS

Range	accXess5 / accXXess10 500 m / 1000 m
Accuracy	2 mm + 2 ppm*
Time	Typ. 2-6 sec
Precise capture	8x20 mm at 50 m

INTERFACE

Keyboard	Full alphanumeric; 25 keys; illuminated (2nd optional)
Display	5" WVGA 800x480 colour and touch with LED backlight
Data recording	2 GB internal memory; removable SD card and USB stick
Ports	Serial; USB; internal Bluetooth®; long-range Bluetooth handle External power and WLAN
Operating system	Microsoft® Windows® EC 7.0

MOTORISATION

Technology	Hybrid Drives
------------	---------------

GeoTRAIL - GNSS based prism search

Speed	100 g/sec
-------	-----------

TRack - Automatic prism logging

Range	800 m at round prism
Max speed	90 km/h at 100m

AiM - Automatic prism fine aiming

Range	1,000 m at round prism
Hz/V accuracy	1"
Technique	Image processing

NAVLIGHT™ - ALIGNMENT AID

Range	5 m to 150 m
Accuracy	5 cm at 100 m

PHYSICAL SPECIFICATIONS

Weight	5.0 - 5.3 kg (w/o battery and tribrach)
Operating- / storage temperature	-20° C to 50° C / -40° C to 70° C
Protection class	IP55 dust and waterproof rating
Humidity	95%, non-condensing

POWER SUPPLY

Internal battery	Removable Li-Ion 4.4 Ah / 7.4 V
Operating time	Up to 8 h **

PLUMMET

Type	Laser point, adjustable brightness
Accuracy	1.5 mm at 1.5 m instrument height

* > 500 m: 4 mm + 2 ppm;

** Battery time may be shorter depending on conditions.



Main Office:
4317 Park Drive Ste 104
Norcross, GA 30093
www.egps.net

o: 770.695.3361
f: 770.695.0803
info@egps.net

GOLD STATUS GEOMAX-AUTHORIZED
TOTAL STATION, ROBOTICS & GPS SERVICE CENTER

GEOMAX Authorised Distribution Partner



Distance meter (Prism Mode): Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1; **Laser plummet:** Laser class 2 in accordance with IEC 60825-1 resp. EN 60825-1,

Distance meter (Non-Prism Mode accXess): Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1



Copyright GeoMax AG.

Illustrations, descriptions and technical specifications are not binding and may change.

All trademarks and trade names are those of their respective owners.

06/21 952870 en